



REVISION HISTORY				
REV	DESCRIPTION	DATE	BY	ECN
17	CREATE INSTALL PRINT	1/25/13	CGL	



- NOTES:**
1. READ OPERATORS MANUAL PRIOR TO INSTALLATION AND OPERATION OF MACHINE
 2. IF MACHINE IS TO BE USED IN ENCLOSED AREAS, A FLUE MUST BE INSTALLED TO VENT BURNER GAS TO OUTSIDE OF ATMOSPHERE. A DRAFT DIVERTER MUST BE INSTALLED TO PERMIT PROPER UPWARD FLOW OF EXHAUST FLUE GASES.
 3. ALL VENTING MUST BE IN ACCORDANCE WITH APPLICABLE FEDERAL AND STATE LAWS, AND LOCAL ORDINANCES. CONSULT LOCAL HEATING CONTRACTORS.
 4. MAX BTU OUTPUT . 365,000 BTU/HR
 5. WATER SUPPLY MUST BE CAPABLE OF PROVIDING A MIN. OF 4.0 GMP @ MAX 65 PSI
 6. ELECTRICAL REQUIREMENT VARY DEPENDING ON ACTUAL MODEL ORDERED, VERIFY REQUIREMENTS WITH SELLING /SERVICING HOTSY DISTRIBUTOR

PROPRIETARY & CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS PROPRIETARY AND MAY CONTAIN TRADE SECRETS AND PATENTABLE SUBJECT MATTER WHICH ARE THE EXCLUSIVE PROPERTY OF KARCHER NORTH AMERICA. THIS DRAWING IS PROTECTED BY THE COPYRIGHT LAWS OF THE UNITED STATES.		KARCHER		CAMAS DESIGN FACILITY 4275 N.W. Pacific Rim Blvd. Camas, Washington 98607 Ph. (360) 833-1600 Fax. (360) 833-9200	
DESCRIPTION HOTSY-900/1400 NG&LP MACHINE LAYOUT					
TOLERANCES UNLESS OTHERWISE NOTED X.XX ± 0.13 X.XXX ± 0.030 X.XXX ± 0.060 (TUBING) X.X° ± 1.0°		SIZE B	MACHINE	DRAWING NUMBER SCV150.IAM	REV 17
DRAWINGS ARE APPROVED VIA ELECTRONIC SIGNATURE IN PLM SYSTEM		SCALE	THIRD ANGLE PROJECTION	SHEET 1 OF 1	
DRAWN SLT	DATE 2/7/2012				